



## Fixed Lens Bullet Cameras



| LENS                    | 3.6MM   | 8MM           |
|-------------------------|---|---------------|
| ANGLE OF VIEW           | 94°   | 42°           |
| IDENTIFICATION DISTANCE | Up to 20 feet   | Up to 40 feet |
| IR ILLUMINATION         | 18 pcs microcrystalline IR LEDs                               |               |
| RESOLUTION              | Full HD 1080p   |               |
| EFFECTIVE PIXELS        | 1920 (H) x 1080 (V)   |               |
| TECHNOLOGY              | HD-TVI, AHD, CVI, CVBS (Selectable)                           |               |
| SIGNAL SYSTEM           | NTSC  |               |
| CONNECTIONS             | 1 x HD BNC Output, 1 x CVBS BNC Output, 1 x 12V DC Connection |               |
| IP RATING               | IP66  |               |
| MOUNT TYPE              | 3-way adjustable mounting bracket                             |               |
| S/N RATIO               | >50dB (AGC Off)   |               |
| WHITE BALANCE           | Auto  |               |
| WIDE DYNAMIC RANGE      | D-WDR   |               |
| DAY/NIGHT               | IR Cut Filter   |               |
| NOISE REDUCTION         | 2D/3D DNR   |               |
| POWER SUPPLY            | 12V DC  |               |
| OPERATING TEMPERATURE   | -4° - 122° F  |               |
| OPERATING HUMIDITY      | < 95% RH (without condensation)                               |               |