



Varifocal Bullet Cameras



LENS	2.8-12MM	6-22MM	5-50MM
ANGLE OF VIEW	103° - 30°	43° - 16°	52° - 7°
IDENTIFICATION DISTANCE	Up to 50 feet	Up to 80 feet	Up to 230 feet
IR ILLUMINATION	3 x 3 rd Generation LEDs	6 x 3 rd Generation IR LEDs	
RESOLUTION		Full HD 1080p	
EFFECTIVE PIXELS		1920 (H) x 1080 (V)	
TECHNOLOGY		HD-TVI, AHD, CVI, CVBS (Selectable)	
SIGNAL SYSTEM		NTSC	
CONNECTIONS		1 x HD BNC Output, 1 x CVBS BNC Output, 1 x 12V DC Connection	
IP RATING		IP66	
MOUNT TYPE		3-way adjustable mounting bracket	
CABLE MANAGEMENT		Cable management bracket included	
S/N RATIO		>50dB (AGC Off)	
WHITE BALANCE		Auto	
WIDE DYNAMIC RANGE		D-WDR	
DAY/NIGHT		IR Cut Filter	
NOISE REDUCTION		2D/3D DNR	
POWER SUPPLY		12V DC	
OPERATING TEMPERATURE		-4° - 122° F	
OPERATING HUMIDITY		< 95% RH (without condensation)	